



12m and 15m Masts LA006 and LA007

AT A GLANCE

The Lencom **LA006** and **LA007** masts are designed to support HF wire antennas, although they can also support VHF and UHF antennas.

Constructed of marine-grade aluminium tubing, each mast comprises either four or five 3m sections.

They are supplied as compact, lightweight assemblies suitable for air freight.

The **LA006** is guyed four ways at the 3m, 6m, 9m and 12m levels, and the **LA007** is guyed four ways at the 3m, 6m, 9m, 12m and 15m levels.

Star pickets are supplied for the guys.

These should be considered temporary, and only for suitable soil types.

Engineered base and anchor points should be used for permanent installations.

Pulleys are supplied to enable an antenna to be raised or lowered.

Lencom can supply gibbets to enable an antenna to be held at a distance from the mast.

A 100mm top spigot to which VHF/UHF antennas can be attached is available as an option. It drops into the top section.

The guys are dielectric rope.



ISO 9001:2008



12m and 15m Masts LA006 and LA007

AT A GLANCE

Specifications

| | LA006 | LA007 |
|-------------------|---|---|
| Height | 12m | 15m |
| Guy radius | 6m | 7m |
| Number of guys | 4 x 4 | 5 x 4 |
| Mast weight | 28.4 kg | 34.5kg |
| Packed weight | 34.4kg | 42kg |
| Packed dimensions | 1 of 3,220mm x 160mm OD tube, containing mast sections and star pickets. 1 of 1,070mm x 410mm x 210mm carton | 1 of 3,220mm x 160mm OD tube, containing mast sections and star pickets. 1 of 1,070mm x 410mm x 210mm carton |
| Wind rating | 150km/h | 150km/h |

Ordering Information

| Part number | Description |
|-------------|-------------------------------------|
| LA006 | 12m mast, c/w installation hardware |
| LA008 | 15m mast, c/w installation hardware |
| | Spigot |
| LA088 | Lightning arrestor kit |

