



Figure 1 – HF bases

The Lencom® 4022 and 4024 are Extremely robust and built to comply with MIL-STD 810. It has Flexible configurations:

- Whips
- Risers
- NVIS kits

Matching fast, reliable ATUs available

Product Information

These Lencom® HF bases and whips are designed to be used with an Automatic Antenna Tuning Unit (ATU), such as the Lencom 4002 or 4006.

They are suitable for mounting on any horizontal, flat surface.

They are extremely rugged and meet MIL-STD 810.

The standard versions are 1.65m, with an optional 800mm riser taking the height to 2.4m.

NVIS kits are available, as is a long wire antenna kit to increase antenna efficiency when stationary.

Refer to the following page for ordering details

Ordering Details

Data Sheet

Part Number	Description
02-4024-001	Flange mount base
02-4022-001	Single hole mount base
02-4019-002	Spring
02-4016-001	1.55m fibreglass whip
02-4020-001	1.65m stainless steel
02-4017-001	800mm riser
01-1008-001	NVIS option for 1.65m whip packages
02-4018-001	NVIS option for 1.65m + 800mm riser packages
60-2174-001	Side-mount bracket option for all packages
46-1010-001	N Plug to UHF Socket Adapter
07-1001-001	6m RF cable, PL259 one end, N plug other end